



Version No: 1037/101/version3

Supersedes: April 11, 2018

Date of issue: April 11, 2018

Document Number 1037/101/version 3:

SECTION 1: Identification of Substance/ Preparation and Company

- 1.1 Product identifier
PES 102 POWERMETAL FLUID ACTIVATOR
- 1.2 Relevant identified uses of the substance or mixture and uses advised against
Aliphatic polyamine hardener blend with inert fillers for repairing metalwork
- 1.3 Details of the supplier of the safety data sheet
5401 HWY 21 W, BRYAN TX. 77803
979-779-8700
Email: pes1@pes-solutions.com
- 1.4 Emergency telephone number
Chemtrec – 800-424-9300 (24 hrs.)

SECTION 2: Hazards Identification

- 2.1 Classification of the substance or mixture
Classification in accordance with the Dangerous Preparations Directive 1999/45/EC

Xn; R20/21/22 Harmful by inhalation, in contact with skin and ifswallowed C; R34 Causes burns
R43 May cause sensitization by skin contact. 3; R68 Possible risk of irreversible effects. 2; R62 Possible risk of impaired fertility
R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in theaquatic environment

Classification in accordance with the Classification Labeling and Packaging Regulation EC

(no) 1272/2008 Acute Toxicity Category 4 H302 Harmful if swallowed
Acute Toxicity Category 4 H312 Harmful in contact with skin
Acute Toxicity Category 4 H332 harmful if inhaled
Skin Corrosive Category 1B H314 Causes severe skin burns and eye damage Eye Damage Category 1 H318 Causes serious eye damage

Skin Sensitizer Category 1

H317 May cause an allergic skin reaction

Mutagen Category 2

H341 Suspected of causing

genetic defects Reproductive Toxicity Category 2 H361f

Suspected of damaging fertility

Aquatic Chronic Category 3

H412 Harmful to aquatic life with long lasting effects

2.2 Label elements

Labeling in accordance with the Classification Labeling and Packaging Regulation EC (no)

1272/2008 Pictograms:



Signal Word:

DANGER

Hazard statements:

H302 + H312 + H332: Harmful if swallowed, in contact with skin or if inhaled.

H314: Causes severe skin burns and eye damage. H317: May cause an allergic skin reaction.

H341: Suspected of causing genetic defects. H361f: Suspected of damaging fertility.

H412 Harmful to aquatic life with long lasting effects

Precautionary statements: P202: Do not handle until all safety precautions have been read and understood. P280: Wear protective gloves/protective clothing/eye protection/face protection.

P305 + P351 + P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310: Immediately call a doctor

P501: Dispose of contents/container as hazardous waste

2.3 Other hazards

May cause chemical burns to the eyes and skin, and if ingested, to the gastrointestinal tract. May cause allergic skin reaction. Prolonged or repeated exposure may result in adverse effects on fertility.

If released into watercourses in sufficient quantities may be harmful to aquatic life. None of the

components are considered to be Persistent, Bioaccumulative and Toxic (PBT) or very Persistent, very Bioaccumulative (vPvB).

SECTION 3: Composition/ Information on Ingredients

3.1 Substances

Not applicable, product is a mixture.

3.2 Mixtures

Contains the following hazardous components above thresholds of concern:

Hazardous Components	Cas Number	%	Classification according to Regulation (EC) No 1272/2008	Classification according to Directive 67/548/EEC
Formaldehyde polymer with Phenol and Triethylenetetramine	32610-77-8	10-30%	Acute Tox. 4 H302 Acute Tox.4 H312, Skin Corr. 1B, skin Sens. 1 H317Aquatic Chronic 3 H412	Xn; R21/22, R43 C; R34 R52/53
Phenol	108-95-2	<10%	Acute Tox. 3 H301, Acute Tox. 3 H311, Acute Tox. 3 H331 Skin Corr. 1B H314, Muta. 2 H341, STOT RE 2 H373	Muta. Cat. 3; R68 T; R23/24/25 Xn; R48/20/21/22 C; R34
Triethylenetetramine	112-24-3	<10%	Acute Tox. 4 H312, Skin Corr. 1B H314, Skin Sens. 1 H317, Aquatic Chronic 3 H412	Xn; R21, R43 C; R34 R52/53
2,2 iminodiethylamine	111-40-0	<10%	Acute Tox. 4 H302, Acute Tox. 4 H312, Acute Tox. 2 H330, Skin Corr. 1B H314, Skin Sens. 1 H317, Eye Dam. 1 H318, STOT SE 3 H335,	T+; R26 Xn; R21/22 C; R34 Xi; R37, R43
Bisphenol A	80-05-7	<10%	Skin Sens. 1 H317, Eye Dam. 1 H318, STOT SE 3 H335, Repr. 2 H361f, Aquatic Chronic 2 H411	Repr. Cat. 3; R62 Xi; R37-41, R43 R52

See section 16 for full description of R phrases and Hstatements.

SECTION 4: First Aid Measures

4.1 Description of first aid measures

Summon immediate medical assistance after contact with skin, eyes, inhalation or ingestion

Eye: Flush eyes with plenty of running water for 15 minutes, whilst gently holding the eyelids open. Seek immediate medical attention.

Skin: Remove product and contaminated clothing and wash area with water, seek medical advice. Except in most minor, superficial or localized burns, cover the affected area with a sterile dressing or clean sheeting.

DO NOT APPLY GREASES OR OINTMENTS. Wash contaminated clothing before re-use.

Ingestion: Drink plenty of water, DO NOT INDUCE VOMITING. Seek medical attention immediately.

Inhalation: Remove patient to fresh air. If breathing has stopped give assisted respiration. Prevent aspiration of vomit. Turn victims head to one side. Seek medical advice.

4.2 Most important symptoms and effects, both acute and delayed

Eye Contact: Sign/ Symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

Skin Contact: Sign/ Symptoms may include localized redness, swelling, itching, intense pain, blistering, ulceration and tissue destruction. Maybe absorbed through skin and cause target organ effects. Persons previously sensitized to amines may develop a cross sensitization reaction to certain other amines *Inhalation:* Sign/ Symptoms may include cough, sneezing, nasal discharge, tightness of chest, headache, hoarseness and nose and throat pain.

Ingestion: Signs/ Symptoms may include severe mouth, throat and abdominal pain, nausea, vomiting and diarrhea, blood in the feces.

4.3 Indication of any immediate medical attention and special treatments needed

Symptomatic treatment as required

SECTION 5: Fire Fighting Measures

5.1 Extinguishing media

Ignition will give rise to class B Fire, in case of fire use Water sprays, Dry chemical, CO2 or Alcohol foam

5.2 Special hazards arising from the substance or mixture

May generate toxic, irritating or flammable combustion products, including nitrogen oxides. Combustion in an oxygen starved environment produces toxic products including nitrites and amides. Sudden reaction and fire may result if mixed with an oxidizing agent.

5.3 Advice for fire fighters

Wear Self-contained breathing apparatus, rubber boots, gloves and body suit

SECTION 6: Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Remove all unnecessary personnel from the area. Ventilate the area if possible. Wear suitable protective clothing including chemical resistant gloves and coveralls. If vapor concentrations are high, respiratory protective equipment may be required. See section 8 for more information.



6.2 Environmental precautions

Prevent entry into sewers and watercourses. If product enters sewers or watercourses, inform the appropriate environmental authorities.

6.3 Methods and materials for containment and cleaning up

Scrape up and transfer into a suitable container. Wash area with water.

6.4 References to other sections

Refer to section 5, 8 and 13 for protective Measures and Disposal.

SECTION 7: Handling and Storage

7.1 Precautions for safe handling

Avoid contact with skin, eyes and clothing. Handle in well ventilated area. Avoid breathing vapors. Wash hands after contact.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a cool, well ventilated area. Keep away from oxidizers, heat or flames.

7.3 Specific end uses(s)

No industrial or sector specific guidance available.

SECTION 8: Exposure Controls/ Personal Protection

8.1 Control parameters

Substance Name	8 hour exposure limit	15 min exposure limit	Notes, Source
2,2'-Iminodi(ethylamine)	1 ppm, 4.3 mg/m ³	—	Sk, EH40, 2011
Bisphenol A inhalable dust	10 mg/m ³	—	EH40, 2011
Phenol	2 ppm, 7.8 mg/m ³	4 ppm, 16 mg/m ³	Sk, EH40, 2011

8.2 Exposure controls

Engineering controls Adequate ventilation should be provided so that exposure limits are not exceeded.

Respiratory: Avoid Breathing Vapors, Mists or Sprays; Select and use respiratory protection. Suggested filter type AP2.

Hand Protection Wear suitable chemical resistant gloves recommended for use with corrosive amines. Nitrile or neoprene gloves may be suitable, but glove manufacturers' specifications should always be checked first. Change gloves in accordance with manufacturer recommendations. If gloves are damaged during use, remove immediately and wash hands before replacing with new gloves.

Skin Protection: Avoid Skin Contact; use disposable coveralls

Eye Protection: Avoid Eye Contact; use safety goggles meeting the requirements of BS EN166 3, when handling this product



Environmental Exposure controls Take suitable measures to prevent entry into drains, sewers and watercourses.

SECTION 9: Physical/ Chemical Properties

9.1 Information on basic physical and chemical properties

Appearance: Amber Fluid
Odor: Ammoniacal, Fishy
Odor threshold: No data
PH: Alkaline
Melting Point: >356F
Boiling Point/ Range: >392F
Flash Point; >212F
Evaporation Rate: No data
Flammability:

Not applicable **Upper/lower flammability limits:** No data **Vapor Pressure:**

No data

Vapor density: No data
Relative density: 1.05g/cm3 at 68F
Solubility in water: Insoluble in water
Solubility in other solvents: No data **Partition Coefficient:** No data **Autoignition temperature:**No data **Decomposition temper**
Explosive properties: Not classified as explosive
Oxidizing properties: Not classified as oxidizing

9.2 Other information

None.

SECTION 10: Stability And Reactivity

10.1 Reactivity
Not considered to be a reactive product
10.2 Chemical stability
Stable
10.3 Possibility of hazardous reactions
Hazardous Polymerization is not likely to occur.
10.4 Conditions to avoid
Excessive heat.
10.5 Incompatible materials



Oxidizing agents – cleaning solutions. Acids - reaction accompanied by large heat release occurs when the product is mixed with acids

10.6 Hazardous decomposition products

Ammonia when heated. Nitrogen Oxides in a fire. Combustion in an oxygen starved environment produces toxic products including nitrites and amides

SECTION 11: Toxicological Information

11.1 Information on toxicological effects

This product has not been tested. Judgments on the expected toxicity of this product have been made based upon consideration of its major components.

(a) acute toxicity	Based on consideration of the components, the mixture is expected to be harmful by inhalation, ingestion or in contact with skin.
(b) skin corrosion/irritation	Based on consideration of the components, the mixture is expected to be corrosive to skin.
(c) serious eye damage/irritation	Based on consideration of the components, the mixture is expected to be corrosive to eyes.
(d) respiratory/skin sensitization	The product contains the following known sensitizers. Formaldehyde polymer with Phenol and Triethylenetetramine, Triethylenetetramine, 2,2 iminodiethylamine (diethylenetetramine), bisphenol A, Persons previously sensitized to amines may develop a cross sensitization reaction to certain other amines.
(e) germ cell mutagenicity	The product contains phenol, which is classified as a suspected mutagen.
(f) carcinogenicity	Contains no substances identified as carcinogens.
(g) reproductive toxicity	The product contains bisphenol A which is suspected of damaging fertility.
(h) STOT-single exposure	This product is corrosive, and is expected to irritate the respiratory tract if inhaled.
(i) STOT-repeated exposure	The product contains phenol, which may cause adverse effects to the liver and kidneys if exposed to significant amounts over a prolonged period of time, at a concentration below the classification threshold for this effect.
(j) aspiration hazard	Not applicable.

SECTION 12: Ecological Information

This product has not been tested. Judgments on the expected toxicity of this product have been made based upon consideration of its major components.

12.1 Toxicity

This product contains components which are considered to be harmful to aquatic organisms and may cause long-term adverse effects in the aquatic environment. Once cured the toxicity of the product is expected to decrease.

12.2 Persistence and degradability



This product is not expected to be readily biodegradable.

12.3 Bioaccumulative potential

This product is expected to have a low bioaccumulation potential.

12.4 Mobility in soil

Cured product is expected to be immobile.

12.5 Results of PBT and vPvB assessment

None of the components are known to be PBT or vPvB.

12.6 Other adverse effects

None known.

SECTION 13: Disposal Considerations

13.1 Waste treatment methods

In uncured state, dispose as chemical waste in accordance with local regulations. Waste from this product may present long term environmental hazards. Thus landfill sites must be considered less acceptable than incineration.

In cured state when mixed correctly with the base component, dispose as

solid waste Empty containers should be disposed of as chemical waste.

SECTION 14: Transport Information

General: Transport and labeling requirements will alter depending on the size of the packaging. Please refer to local transport regulations.

	ADR	IMDG	ICAO
14.1 UN Number	2735	2735	2735
14.2 UN Proper shipping name	Polyamines, liquid, corrosive, N.O.S. (Contains Triethylene tetramine, Diethylenetriamine)	Polyamines, liquid, corrosive, N.O.S. (Contains Triethylene tetramine, Diethylenetriamine)	Polyamines, liquid, corrosive, N.O.S. (Contains Triethylene tetramine, Diethylenetriamine)
14.3 Transport hazard class(es)	8	8	8
14.4 Packing group	III	III	III
14.5 Environmental hazards	Not EHS	Not EHS	Not EHS
14.6 Special precautions for user	HIN 80 Tunnel Code E	EmS F-A, S-B	None
14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable	Not applicable	Not applicable



SECTION 15: Regulatory Information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

All components are listed as existing substances in Europe

All components are listed, or are exempt from listing on the TCSA Inventory

15.2 Chemical Safety Assessment

A Chemical Safety Assessment has not been carried out for this product.

SECTION 16: Other Information

Revision information:

Reformatted in accordance with Regulation 453/2010 and Regulation 1272/2008.

List of Abbreviations used in this SDS:

CAS Chemical Abstracts Service

CLP Classification, Labeling and Packaging Regulation (EC)

no 1272/2008 DSD Dangerous Substances Directive
67/548/EEC

DPD Dangerous Preparations

Directive 1999/45/EC EC European
Community/Commission

PBT Persistent, Bioaccumulative and Toxic

REACH Registration, Evaluation, Authorization and Restriction of Chemicals Regulation (EC)

no 1907/2006 vPvB very Persistent, very Bioaccumulative

References:

ECHA Classification and Labeling inventory

ECHA database of disseminated

registration dossiers Supplier's Safety

Data Sheets

Method used for classification of mixtures:

Ingredient based approaches

R Phrases and H Statements used in Section 3

R20/22 Harmful by inhalation and if

swallowed, R21/22 Harmful in contact with

skin and if swallowed, R22 Harmful if

swallowed,

R23/24/25; Toxic by inhalation, in contact with skin and



Safety Data Sheet

if swallowed, R26 Very toxic if inhaled

- R34 Causes burns
- R36 Irritating to eyes
- R36/38 Irritating to eyes and skin,
- R37 Irritating to respiratory system,
- R41 Risk of serious damage to eyes,
- R43 May cause sensitization by skin contact
- R48/20/21/22; Harmful: Danger of serious damage to health by prolonged exposure through inhalation, in contact with skin and if swallowed.
- R52 Harmful to aquatic organisms
- R52/53 Harmful to aquatic organisms, may cause long term adverse effects in the aquatic environment, R62 Possible risk of impaired fertility
- R68 Possible risk of irreversible effects
- H301 Toxic if swallowed
- H302 Harmful if swallowed
- H311 Toxic in contact with skin
- H312 Harmful in contact with skin
- H314 Causes severe skin burns and eye damage
- H317 May cause an allergic skin reaction
- H318 Causes serious eye damage H319
- H330 Fatal if inhaled
- H331 Toxic if inhaled
- H332 Harmful if inhaled
- H335 May cause respiratory irritation
- H341 Suspected of causing genetic defects
- H361f Suspected of damaging fertility
- H373 May cause damage to organs through prolonged or repeated exposure H411 Toxic to aquatic life with long lasting effects
- H412 Harmful to aquatic life with long lasting effects

Training requirements for workers

No special training requirements.

Date of issue: January 14, 2015

Document Number 1037/101/version 3:

SECTION 1: Identification of Substance/ Preparation and Company

- 1.2 Product identifier
PES 102 POWERMETAL FLUID BASE
- 1.2 Relevant identified uses of the substance or mixture and uses advised against
Epoxy Resin with inert metallic fillers
- 1.3 Details of the supplier of the safety data sheet
5401 HWY 21 W, BRYAN, TX. 77803
Tel: 979-779-8700
Email: pes1@pes-solutions.com
- 1.4 Emergency telephone number
Chemtrec – 800-424-9300 (24 hrs.)

SECTION 2: Hazards Identification

- 2.1 Classification of the substance or mixture

Classification in accordance with the Dangerous Preparations

Directive 1999/45/EC Xi; R36/38	Irritating to eyes and
skin	
R43	May cause sensitization by skin contact
N; R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

environment Classification in accordance with the Classification Labeling and Packaging Regulation EC

(no) 1272/2008

Skin Irritant Category 2	H315 Causes skin irritation
Eye Irritant Category 2	H319 Causes serious eye irritation
Skin Sensitizer Category 1	H317 May cause an allergic skin reaction
Aquatic Chronic Category 2	H411 Toxic to aquatic life with long lasting effects

- 2.2 Label elements

Labeling in accordance with the Classification Labeling and Packaging Regulation EC (no) 1272/2008

Pictograms:





Safety Data Sheet

Signal Word: WARNING

Hazard statements: H315 Causes skin irritation
H319 Causes serious eye irritation
H317 May cause an allergic skin reaction
H411 Toxic to aquatic life with long lasting effects

Precautionary statements: P280: Wear protective gloves/protective clothing/eye protection/face protection .

P305 + P351 + P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313 If eye irritation persists: Get medical advice/attention. P501: Dispose of contents/container as hazardous waste

2.3 Other hazards

May cause irritation to the eyes and skin, and if ingested, to the gastrointestinal tract. May cause allergic skin reaction. If released into watercourses in sufficient quantities may be toxic to aquatic life. None of the components are considered to be Persistent, Bioaccumulative and Toxic (PBT) or very Persistent, very Bioaccumulative (vPvB).

SECTION 3: Composition/ Information on Ingredients

3.1 Substances

Not applicable, product is a mixture.

3.2 Mixtures

Contains the following hazardous components above thresholds of concern:

Hazardous Components	Cas Number	%	Classification according to Regulation (EC) No 1272/2008	Classification according to Directive 67/548/EEC
Reaction product Bisphenol F- (epichlorhydrin)	28064-14-4	10-30%	Skin Irrit. 2 H315, Skin Sens. 1 H317, Aquatic Chronic 2 H411	Xi; R38-43-51/53

Reaction product bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)	25068-38-6	10-30%	Skin Irrit. 2 H315, Eye Irrit. 2 H319, Skin Sens. 1 H317, Aquatic Chronic 2 H411	Xi; R36/38-43-51/53
--	------------	--------	--	---------------------

See section 16 for full description of R phrases and Hstatements.

SECTION 4: First Aid Measures

4.1 Description of first aid measures

Summon immediate medical assistance after contact with skin, eyes, inhalation or ingestion

Eye: Flush eyes with plenty of running water for several minutes, whilst gently holding the eyelids open. Seek medical attention if irritation persists.

Skin: Remove product and contaminated clothing and wash area with water, seek medical advice. Wash contaminated clothing before re-use.

Ingestion: Drink plenty of water, DO NOT INDUCE VOMITING. Seek medical attention immediately.

Inhalation: Remove patient to fresh air. If breathing has stopped give assisted respiration. Prevent aspiration of vomit. Turn victims head to one side. Seek medical advice.

4.2 Most important symptoms and effects, both acute and delayed

Eye Contact: Sign/ Symptoms may include redness, tearing, pain.

Skin Contact: Sign/ Symptoms may include localized redness, swelling, itching

Inhalation: Sign/ Symptoms may include cough, sneezing, nasal discharge, tightness of chest, headache, hoarseness and nose and throat irritation.

Ingestion: Signs/ Symptoms may include irritation of the mouth, throat, nausea, vomiting.

4.3 Indication of any immediate medical attention and special treatments needed

Symptomatic treatment as required

SECTION 5: Fire Fighting Measures

5.1 Extinguishing media

Ignition will give rise to class B Fire, in case of fire use Water sprays, Dry chemical, CO2 or Alcohol foam

5.2 Special hazards arising from the substance or mixture

Sudden reaction and fire may result if mixed with an oxidizing agent.

5.3 Advice for fire fighters

Wear Self-contained breathing apparatus, rubber boots, gloves and body suit



SECTION 6: Accidental Release Measures

- 6.1 Personal precautions, protective equipment and emergency procedures**
Remove all unnecessary personnel from the area. Ventilate the area if possible. Wear suitable protective clothing including chemical resistant gloves and coveralls. If vapor concentrations are high, respiratory protective equipment may be required. See section 8 for more information.
- 6.2 Environmental precautions**
Prevent entry into sewers and watercourses. If product enters sewers or watercourses, inform the appropriate environmental authorities.
- 6.3 Methods and materials for containment and clearing up**
Scrape up and transfer into a suitable container. Wash area with water.
- 6.4 References to other sections**
Refer to section 5, 8 and 13 for Protective Measures and Disposal.

SECTION 7: Handling and Storage

- 7.1 Precautions for safe handling**
Avoid contact with skin, eyes and clothing. Handle in well ventilated area. Avoid breathing vapors. Wash hands after contact.
- 7.2 Conditions for safe storage, including any incompatibilities**
Keep container tightly closed in a cool, well ventilated area. Keep away from oxidizers, heat or flames.
- 7.4 Specific end uses(s)**
No industrial or sector specific guidance available.

SECTION 8: Exposure Controls/ Personal Protection

8.1 Control parameters

Substance Name	8 hour exposure limit	15 min exposure limit	Notes, Source
Talc (magnesium silicate), respirable dust	1 mg/m ³	—	EH40, 2011

8.2 Exposure controls

- Engineering controls** Adequate ventilation should be provided so that exposure limits are not exceeded.
- Respiratory:** Not normally required. If significant aerosols are likely to be generated a suitable respirator may be required. Suggested filter type AP2.
- Hand Protection** Wear suitable chemical resistant gloves. Nitrile or neoprene gloves may be suitable, but glove manufacturers' specifications should always be checked first. Change gloves in accordance with manufacturer recommendations. If gloves are



damaged during use, remove immediately and wash hands before replacing with new gloves.

Skin Protection: Avoid Skin Contact; use disposable coveralls

Eye Protection: Avoid Eye Contact; use safety goggles meeting the requirements of BS EN166 3, when handling this product

Environmental Exposure controls Take suitable measures to prevent entry into drains, sewers and watercourses.

SECTION 9: Physical/ Chemical Properties

9.1 Information on basic physical and chemical properties

- Appearance:** Grey Paste
- Odor:** Weak
- Odor threshold:** No data
- PH:** Neutral
- Melting Point:** No data
- Boiling Point/ Range:** 338F
- Flash Point;** >302F
- Evaporation Rate:** No data
- Flammability:**

Not applicable **Upper/lower flammability limits:** No data **Vapor Pressure:**

- No data
- Vapor density:** No data
- Relative density:** 2.7g/cm³ at 68F
- Solubility in water:** Insoluble in water
- Solubility in other solvents:** Soluble in organic solvents
- Partition Coefficient:** Log Kow 3-5 (estimated) (Bisphenol A/F epoxy resin)
- Autoignition temperature:** Above boiling point
- Decomposition temperature:** No data
- Viscosity:** Thick paste
- Explosive properties:** Not classified as explosive
- Oxidizing properties:** Not classified as oxidizing

9.2 Other information
None.



SECTION 10: Stability And Reactivity

- 10.1 Reactivity**
Not considered to be a reactive product
- 10.2 Chemical stability**
Stable
- 10.3 Possibility of hazardous reactions**
Hazardous Polymerization is not likely to occur.
- 10.4 Conditions to avoid**
Excessive heat.
- 10.5 Incompatible materials**
Acids - reaction accompanied by large heat release occurs when the product is mixed with acids
- 10.6 Hazardous decomposition products**
None identified.

SECTION 11: Toxicological Information

11.1 Information on toxicological effects
This product has not been tested. Judgments on the expected toxicity of this product have been made based upon consideration of its major components.

(a) acute toxicity	Based on consideration of the components, the mixture is not expected to be harmful by inhalation, ingestion or in contact with skin. The ATE for the mixture is expected to be >2000 mg/kg
(b) skin corrosion/irritation	Based on consideration of the components, the mixture is expected to be irritating to skin.
(c) serious eye damage/irritation	Based on consideration of the components, the mixture is expected to be irritating to eyes.
(d) respiratory/skin sensitization	The product contains the following known sensitizers: Bisphenol A epoxy resin, Persons previously sensitized to amines may develop a cross sensitization reaction to certain other amines.
(e) germ cell mutagenicity	Contains no substances identified as mutagens.
(f) carcinogenicity	Contains no substances identified as carcinogens.
(g) reproductive toxicity	Resins based on Bisphenol A did not cause adverse effects in animal tests.
(h) STOT-single exposure	Target organ toxicity is not expected with this product.
(i) STOT-repeated exposure	Target organ toxicity is not expected with this product.
(j) aspiration hazard	Not applicable.

SECTION 12: Ecological Information

This product has not been tested. Judgments on the expected toxicity of this product have been made based upon consideration of its major components.

12.1 Toxicity
This product contains components which are considered to be toxic to aquatic organisms and may cause



long-term adverse effects in the aquatic environment. Once cured the toxicity of the product is expected to decrease.

Data for Component: Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <=700)

Fish Acute & Prolonged Toxicity

LC50, Oncorhynchus mykiss (rainbow trout), semi-static test, 96

h: 2 mg/l Aquatic Invertebrate Acute Toxicity

EC50, Daphnia magna (Water flea), static test, 48 h,

immobilization: 1.8 mg/l Aquatic Plant Toxicity

ErC50, Scenedesmus capricornutum (fresh water algae), static test, Growth rate inhibition, 72 h:

11 mg/l Toxicity to Micro-organisms

IC50; Bacteria, 18 h: >

42.6 mg/l Aquatic Invertebrates

Chronic Toxicity Value

Daphnia magna (Water flea), semi-static test, 21 d, number of offspring, NOEC: 0.3 mg/l

12.2 Persistence and degradability

This product is not expected to be readily biodegradable.

Data for Component: Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)

Biodegradation	Exposure Time	Method
	10 Day Window	12 %
	28 d	OECD 302B Test
Not applicable		

12.3 Bioaccumulative potential

This product is expected to have a low-moderate bioaccumulation potential.

12.4 Mobility in soil

Mobility of the uncured product is expected to be low. Cured product is expected to be immobile.

12.5 Results of PBT and vPvB assessment

None of the components are known to be PBT or vPvB.

12.6 Other adverse effects

None known.

SECTION 13: Disposal Considerations

13.1 Waste treatment methods

In uncured state, dispose as chemical waste in accordance with local regulations. Waste from this product



may present long term environmental hazards. Thus landfill sites must be considered less acceptable than incineration.

In cured state when mixed correctly with the activator component, dispose as

solid waste Empty containers should be disposed of as chemical waste.

SECTION 14: Transport Information

General: Transport and labeling requirements will alter depending on the size of the packaging. Please refer to local transport regulations.

	ADR	IMDG	ICAO
14.1 UN Number	3077	3077	3077
14.2 UN Proper shipping name	Environmentally hazardous substance, solid, N.O.S. (epoxy resin)	Environmentally hazardous substance, solid, N.O.S. (epoxy resin)	Environmentally hazardous substance, solid, N.O.S. (epoxy resin)
14.3 Transport hazard class(es)	9	9	9
14.4 Packing group	III	III	III
14.5 Environmental hazards	Environmentally hazardous	Marine Pollutant	Environmentally hazardous
14.6 Special precautions for user	HIN 90	EmS F-A, S-F	None
14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable	Not applicable	Not applicable

SECTION 15: Regulatory Information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

All components are listed as existing substances in Europe
 All components are listed, or are exempt from listing on the TCSA Inventory

15.2 Chemical Safety Assessment

A Chemical Safety Assessment has not been carried out for this product.

SECTION 16: Other Information

Revision information:

Reformatted in accordance with Regulation 453/2010 and Regulation 1272/2008.

List of Abbreviations used in this SDS:

CAS Chemical Abstracts Service



Safety Data Sheet

CLP	Classification, Labeling and Packaging Regulation (EC) no 1272/2008
DSD	Dangerous Substances Directive 67/548/EEC
DPD	Dangerous Preparations Directive 1999/45/EC
EC	European Community/Commission
PBT	Persistent, Bioaccumulative and Toxic
REACH	Registration, Evaluation, Authorization and Restriction of Chemicals Regulation (EC) no 1907/2006
vPvB	very Persistent, very Bioaccumulative

References:

ECHA Classification and Labeling inventory
ECHA database of disseminated registration dossiers Supplier's Safety Data Sheets

Method used for classification of mixtures:

Ingredient based approaches

R Phrases and H Statements used in Section 3

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.
R36/38	Irritating to eyes and skin.
R38	May be irritating to skin
R43	May cause sensitization by skin contact.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Training requirements for workers

No special training requirements.