



## Safety Data Sheet

Version No: 1037/101/version3

Supersedes: April 11, 2018

**PRODUCT NAME:** PES 106 POWER METAL PASTE XF

**DISTRIBUTOR:** Plant Equipment & Svcs,  
5401 HWY 21 W, Bryan, TX.77803 United States

**TELEPHONE NUMBER:** 979-779-8700

**E: mail** pes1@pes-solutions.com

**EMERGENCY TELEPHONE NUMBER: Chemtrec – 800-424-9300 (24 hrs.)**

THIS PRODUCT IS A KIT AND SUPPLIED AS A MULTI PART PRODUCT WHICH CONSISTS OF A BASE COMPONENT AND ACTIVATOR COMPONENT. THIS DOCUMENT CONTAINS THE MSDS FOR BOTH BASE AND ACTIVATOR COMPONENTS.

*DISCLAIMER: The information supplied in the SDS is correct at the time of writing and date of issue. No warranties, expressed or implied, including, but not limited to, any implied warranty of merchantability or fitness for particular purpose or course of performance or usage of trade. The user of the material is responsible for ensuring the suitability of this product for application.*

## SECTION 1: Identification of Substance/ Preparation and Company

- 1.1 Product identifier  
**PES 106 POWER METAL PASTE XF ACTIVATOR**
- 1.2 Relevant identified uses of the substance or mixture and uses advised against  
Polymercaptan Curing Agent
- 1.3 Details of the supplier of the safety data sheet  
5401 Hwy 21 West Bryan, TX 77803  
Tel: (979)779-8700  
Email: pes1@pes-solutions.com
- 1.4 Emergency telephone number  
Chemtrec – 800-424-9300 (24 hrs.)

## SECTION 2: Hazards Identification

- 2.1 Classification of the substance or mixture  
Classification in accordance with the Dangerous Preparations Directive 1999/45/EC
- |  |            |
|--|------------|
| Skin Irritation  | Category 2 |
| H315 Causes skin irritation                            |            |
| Serious Eye Irritation                                 | Category 2 |
| H319 Causes Serious Eye Irritation                     |            |
| Skin Sensitizer  | Category 1 |
| H317 May Cause an allergic Skin Reaction               |            |
| Chronic Hazards to the Aquatic Environment             | Category 3 |
| H412 Harmful to Aquatic life with long lasting effects |            |
- Sensitizing
- R43 May cause sensitization by skin contact
- Xi – irritant
- R36/38 irritating to eyes and skin
- Dangerous to the environment
- R52/53 Harmful to aquatic organisms, may cause long term adverse effects in the aquatic environment
- Xn; R20/21/22 Harmful by inhalation, in contact with skin and if swallowed
- C; R34 Causes burns
- R43 May cause sensitization by skin contact
- Muta. 3; R68 Possible risk of irreversible effects
- Repr. 2; R62 Possible risk of impaired fertility
- R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment

## 2.2 Label elements

Labeling in accordance with the Classification Labeling and Packaging Regulation EC (no) 1272/2008

Pictograms:



Signal Word:

**WARNING**

Hazard statements:

H315: Causes skin irritation.  
H317: May cause an allergic skin reaction.  
H319: Causes serious eye irritation  
H412 Harmful to aquatic life with long lasting effects

Precautionary statements:

P101: if medical advice is needed have product container or label at hand  
P102: Keep out of reach of children  
P501: Dispose of waste and residues in accordance with local authority requirements

Precautionary statements:

**PREVENTION**

P273: Avoid release to the environment  
P280 Wear protective gloves

Precautionary statements:

**RESPONSE**

P302+P352 IF ON SKIN: Wash with plenty soap and water  
P333+P313: If skin irritation or rash occurs: Get medical advice/ attention  
P337+ P313: If eye irritation persists: Get medical advice/ attention

## 2.3 Other hazards

If released into watercourses in sufficient quantities may be harmful to aquatic life. None of the components are considered to be Persistent, Bioaccumulative and Toxic (PBT) or very Persistent, very Bioaccumulative (vPvB).

## SECTION 3: Composition/ Information on Ingredients

### 3.1 Substances

Not applicable, product is a mixture.

### 3.2 Mixtures

Contains no hazardous materials above the required thresholds  
See section 16 for full description of R phrases and H statements.

## SECTION 4: First Aid Measures

### 4.1 Description of first aid measures

*Summon immediate medical assistance after contact with skin, eyes, inhalation or ingestion*

**Eye:** Flush eyes with plenty of running water for 15 minutes, whilst gently holding the eyelids open.

**Skin:** Remove product and contaminated clothing and wash area with water.  
**Ingestion:** Drink plenty of water, DO NOT INDUCE VOMITING. Seek medical attention immediately.  
**Inhalation:** Remove patient to fresh air. Seek medical advice.

**4.2 Most important symptoms and effects, both acute and delayed**

**SKIN:** Redness, Inflammation  
**SKIN:** Rash, Urticaria  
**EYE:** Irritation, Conjunctivitis

**4.3 Indication of any immediate medical attention and special treatments needed**

Symptomatic treatment as required

**SECTION 5: Fire Fighting Measures**

**5.1 Extinguishing media**

Dry chemical, CO2 or Alcohol foam

**5.2 Special hazards arising from the substance or mixture**

In the event of fire carbon monoxide, carbon dioxide and nitrogen oxides can be released

**5.3 Advice for fire fighters**

Wear Self-contained breathing apparatus, rubber boots, gloves and body suit

**SECTION 6: Accidental Release Measures**

**6.1 Personal precautions, protective equipment and emergency procedures**

Avoid skin and eye contact

**6.2 Environmental precautions**

Prevent entry into sewers and watercourses. If product enters sewers or watercourses, inform the appropriate environmental authorities.

**6.3 Methods and materials for containment and clearing up**

Scrape up and transfer into a suitable container. Wash area with water.

**6.4 References to other sections**

Refer to section 5, 8 and 13 for protective Measures and Disposal.

**SECTION 7: Handling and Storage**

**7.1 Precautions for safe handling**

Avoid contact with skin, eyes and clothing. Handle in well ventilated area. Wash hands after contact.

**7.2 Conditions for safe storage, including any incompatibilities**

Keep container tightly closed in a cool, well ventilated area.

**7.3 Specific end uses(s)**

No industrial or sector specific guidance available.

**SECTION 8: Exposure Controls/ Personal Protection**

**8.1 Control parameters**

Substance Name	8 hour exposure limit	15 min exposure limit	Notes, Source



## Safety Data Sheet

Talc, Respirable dust 14807-96-6	-	—	EH40 WEL
-------------------------------------	---	---	----------

### 8.2 Exposure controls

- Engineering controls** Adequate ventilation should be provided so that exposure limits are not exceeded.
- Respiratory:** Avoid Breathing Vapors, Mists or Sprays; Select and use respiratory protection. Suggested filter type AP2.
- Hand Protection** Wear suitable chemical resistant gloves recommended. Nitrile or neoprene gloves may be suitable, but glove manufacturers' specifications should always be checked first. Change gloves in accordance with manufacturer recommendations. If gloves are damaged during use, remove immediately and wash hands before replacing with new gloves.
- Skin Protection:** Avoid Skin Contact; use disposable coveralls
- Eye Protection:** Avoid Eye Contact; use safety goggles meeting the requirements of BS EN166 3, when handling this product
- Environmental Exposure controls** Take suitable measures to prevent entry into drains, sewers and watercourses.

## SECTION 9: Physical/ Chemical Properties

### 9.1 Information on basic physical and chemical properties

- Appearance:** Paste
- Odor:** Strong
- Odor threshold:** No data
- PH:** No data
- Melting Point:** >356°F
- Boiling Point/ Range:** >167°F
- Flash Point;** >212°F
- Evaporation Rate:** No data
- Flammability:** Not applicable
- Upper/lower flammability limits:** No data
- Vapor Pressure:** No data
- Vapor density:** No data
- Relative density:** 1.8g/cm<sup>3</sup> at 68°F
- Solubility in water:** Insoluble in water
- Solubility in other solvents:** No data
- Partition Coefficient:** No data
- Autoignition temperature:** No data
- Decomposition temperature:** No data
- Viscosity:** No data
- Explosive properties:** Not classified as explosive
- Oxidizing properties:** Not classified as oxidizing

### 9.2 Other information

None.

## **SECTION 10: Stability And Reactivity**

### **10.1 Reactivity**

Reaction with strong acids  
Reacts with strong oxidants

### **10.2 Chemical stability**

Stable

### **10.3 Possibility of hazardous reactions**

Hazardous Polymerization is not likely to occur.

### **10.4 Conditions to avoid**

None if used for intended purpose

### **10.5 Incompatible materials**

See section reactivity

### **10.6 Hazardous decomposition products**

None known

## **SECTION 11: Toxicological Information**

### **11.1 Information on toxicological effects**

This product has not been tested. Judgments on the expected toxicity of this product have been made based upon consideration of its major components.

(a) acute toxicity	LD50 >200mg/kg ORAL Rat
(b) skin corrosion/irritation	LD50 23.000 mg/kg DERMAL Rabbit
(c) serious eye damage/irritation	Not irritating. Rabbit. OECD Guideline 405 (Acute eye irritation/ corrosion)
(d) respiratory/skin sensitisation	Sensitising. Mouse local lymphnode assay (LLNA) OECD Guideline 472 (Genetic toxicology: Escherichia Coli Reverse Mutation Assay)
(e) germ cell mutagenicity	Negative. Bacterial reversemutation assay (e.g Ames test). OECD Guideline 472) Genetic Toxicology Escherichia Coli Reverse Mutation Assay)
(f) carcinogenicity	Contains no substances identified as carcinogens.

## **SECTION 12: Ecological Information**

This product has not been tested. Judgments on the expected toxicity of this product have been made based upon consideration of its major components.

### **12.1 Toxicity**



This product contains components which are considered to be harmful to aquatic organisms and may cause long-term adverse effects in the aquatic environment. Once cured the toxicity of the product is expected to decrease.

**12.2 Persistence and degradability**

This product is not expected to be readily biodegradable.

**12.3 Bioaccumulative potential**

This product is expected to have a low bioaccumulation potential.

**12.4 Mobility in soil**

Cured product is expected to be immobile.

**12.5 Results of PBT and vPvB assessment**

None of the components are known to be PBT or vPvB.

**12.6 Other adverse effects**

None known.

**SECTION 13: Disposal Considerations**

**13.1 Waste treatment methods**

In uncured state, dispose as chemical waste in accordance with local regulations. Waste from this product may present long term environmental hazards. Thus landfill sites must be considered less acceptable than incineration.

In cured state when mixed correctly with the base component, dispose as solid waste

Empty containers should be disposed of as chemical waste.

**SECTION 14: Transport Information**

**General:** Transport and labeling requirements will alter depending on the size of the packaging. Please refer to local transport regulations.

	ADR	IMDG	ICAO
14.1 UN Number	Not Hazardous	Not Hazardous	Not Hazardous
14.2 UN Proper shipping name	Not Hazardous	Not Hazardous	Not Hazardous
14.3 Transport hazard class(es)	Not Hazardous	Not Hazardous	Not Hazardous
14.4 Packing group	Not Hazardous	Not Hazardous	Not Hazardous
14.5 Environmental hazards	Not Hazardous	Not Hazardous	Not Hazardous
14.6 Special precautions for user	Not Hazardous	Not Hazardous	Not Hazardous
14.7 Transport in bulk	Not applicable	Not applicable	Not applicable

according to Annex II of MARPOL 73/78 and the IBC Code			
--	--	--	--

### **SECTION 15: Regulatory Information**

#### **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

All components are listed as existing substances in Europe

All components are listed, or are exempt from listing on the TCSA Inventory

#### **15.2 Chemical Safety Assessment**

A Chemical Safety Assessment has not been carried out for this product.

### **SECTION 16: Other Information**

#### **Revision information:**

Reformatted in accordance with Regulation 453/2010 and Regulation 1272/2008.

#### **List of Abbreviations used in this SDS:**

CAS Chemical Abstracts Service

CLP Classification, Labeling and Packaging Regulation (EC) no 1272/2008

DSD Dangerous Substances Directive 67/548/EEC

DPD Dangerous Preparations Directive 1999/45/EC

EC European Community/Commission

PBT Persistent, Bioaccumulative and Toxic

REACH Registration, Evaluation, Authorization and Restriction of Chemicals Regulation (EC) no 1907/2006

vPvB very Persistent, very Bioaccumulative

#### **References:**

ECHA Classification and Labeling inventory

ECHA database of disseminated registration dossiers

Supplier's Safety Data Sheets

#### **Method used for classification of mixtures:**

Ingredient based approaches

#### **R Phrases and H Statements used in Section 3**

R36/38 Irritating to eyes and skin,

R43 May cause sensitization by skin contact

R52 Harmful to aquatic organisms

R52/53 Harmful to aquatic organisms, may cause long term adverse effects in the aquatic environment,

H315 Causes skin irritation

H317 May cause an allergic skin reaction

H319 Causes serious eye damage

H411 Toxic to aquatic life with long lasting effects

H412 Harmful to aquatic life with long lasting effects

#### **Training requirements for workers**

No special training requirements.



## SECTION 1: Identification of Substance/ Preparation and Company

- 1.2 Product identifier  
**PES 106 POWER METAL PASTE XF BASE**
- 1.2 Relevant identified uses of the substance or mixture and uses advised against  
Epoxy Resin with inert talcs and fillers
- 1.3 Details of the supplier of the safety data sheet  
5401 Hwy 21 West Bryan, TX 77803  
Tel: (979)779-8700  
Email: pes1@pes-solutions.com
- 1.4 Emergency telephone number  
Chemtrec – 800-424-9300 (24 hrs.)

## SECTION 2: Hazards Identification

- 2.1 Classification of the substance or mixture  
Classification in accordance with the Dangerous Preparations Directive 1999/45/EC

Xi; R36/38 Irritating to eyes and skin  
R43 May cause sensitization by skin contact  
N; R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment

Classification in accordance with the Classification Labeling and Packaging Regulation EC (no) 1272/2008

Skin Irritant Category 2 H315 Causes skin irritation  
Eye Irritant Category 2 H319 Causes serious eye irritation  
Skin Sensitizer Category 1 H317 May cause an allergic skin reaction  
Aquatic Chronic Category 2 H411 Toxic to aquatic life with long lasting effects

- 2.2 Label elements  
Labeling in accordance with the Classification Labeling and Packaging Regulation EC (no) 1272/2008



Pictograms:

Signal Word:

**WARNING**

Hazard statements:

H315 Causes skin irritation  
H319 Causes serious eye irritation  
H317 May cause an allergic skin reaction  
H411 Toxic to aquatic life with long lasting effects

**Precautionary statements: P280: Wear protective gloves/protective clothing/eye protection/face protection.**  
**P305 + P351 + P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.**  
**P337 + P313 If eye irritation persists: Get medical advice/attention.**  
**P501: Dispose of contents/container as hazardous waste**

**2.3 Other hazards**

May cause irritation to the eyes and skin, and if ingested, to the gastrointestinal tract. May cause allergic skin reaction. If released into watercourses in sufficient quantities may be toxic to aquatic life. None of the components are considered to be Persistent, Bioaccumulative and Toxic (PBT) or very Persistent, very Bioaccumulative (vPvB).

**SECTION 3: Composition/ Information on Ingredients**

**3.1 Substances**

Not applicable, product is a mixture.

**3.2 Mixtures**

Contains the following hazardous components above thresholds of concern:

Hazardous Components	Cas Number	%	Classification according to Regulation (EC) No 1272/2008	Classification according to Directive 67/548/EEC
Reaction product Bisphenol F- (epichlorhydrin)	28064-14-4	10-30%	Skin Irrit. 2 H315, Skin Sens. 1 H317, Aquatic Chronic 2 H411	Xi; R38-43-51/53
Reaction product bisphenol-A- (epichlorhydrin) epoxy resin (number average molecular weight <= 700)	25068-38-6	10-30%	Skin Irrit. 2 H315, Eye Irrit. 2 H319, Skin Sens. 1 H317, Aquatic Chronic 2 H411	Xi; R36/38-43-51/53

See section 16 for full description of R phrases and H statements.

**SECTION 4: First Aid Measures**

**4.1 Description of first aid measures**

*Summon immediate medical assistance after contact with skin, eyes, inhalation or ingestion*

- Eye:** Flush eyes with plenty of running water for several minutes, whilst gently holding the eyelids open. Seek medical attention if irritation persists.
- Skin:** Remove product and contaminated clothing and wash area with water, seek medical advice. Wash contaminated clothing before re-use.
- Ingestion:** Drink plenty of water, DO NOT INDUCE VOMITING. Seek medical attention immediately.
- Inhalation:** Remove patient to fresh air. If breathing has stopped give assisted respiration. Prevent aspiration of vomit. Turn victims head to one side. Seek medical advice.

**4.2 Most important symptoms and effects, both acute and delayed**

*Eye Contact:* Sign/ Symptoms may include redness, tearing, and pain.

*Skin Contact:* Sign/ Symptoms may include localized redness, swelling, itching  
*Inhalation:* Sign/ Symptoms may include cough, sneezing, and nasal discharge, tightness of chest, headache, hoarseness and nose and throat irritation.  
*Ingestion:* Signs/ Symptoms may include irritation of the mouth, throat, nausea, vomiting.

**4.3 Indication of any immediate medical attention and special treatments needed**  
 Symptomatic treatment as required

**SECTION 5: Fire Fighting Measures**

- 5.1 Extinguishing media**  
 Ignition will give rise to class B Fire, in case of fire use Water sprays, Dry chemical, CO2 or Alcohol foam
- 5.2 Special hazards arising from the substance or mixture**  
 Sudden reaction and fire may result if mixed with an oxidizing agent.
- 5.3 Advice for fire fighters**  
 Wear Self-contained breathing apparatus, rubber boots, gloves and body suit

**SECTION 6: Accidental Release Measures**

- 6.1 Personal precautions, protective equipment and emergency procedures**  
 Remove all unnecessary personnel from the area. Ventilate the area if possible. Wear suitable protective clothing including chemical resistant gloves and coveralls. If vapor concentrations are high, respiratory protective equipment may be required. See section 8 for more information.
- 6.2 Environmental precautions**  
 Prevent entry into sewers and watercourses. If product enters sewers or watercourses, inform the appropriate environmental authorities.
- 6.3 Methods and materials for containment and clearing up**  
 Scrape up and transfer into a suitable container. Wash area with water.
- 6.4 References to other sections**  
 Refer to section 5, 8 and 13 for Protective Measures and Disposal.

**SECTION 7: Handling and Storage**

- 7.1 Precautions for safe handling**  
 Avoid contact with skin, eyes and clothing. Handle in well ventilated area. Avoid breathing vapors. Wash hands after contact.
- 7.2 Conditions for safe storage, including any incompatibilities**  
 Keep container tightly closed in a cool, well ventilated area. Keep away from oxidizers, heat or flames.
- 7.4 Specific end uses(s)**  
 No industrial or sector specific guidance available.

**SECTION 8: Exposure Controls/ Personal Protection**

**8.1 Control parameters**

Substance Name	8 hour exposure limit	15 min exposure limit	Notes, Source
Talc (magnesium silicate), respirable dust	1 mg/m <sup>3</sup>	—	EH40, 2011

## 8.2 Exposure controls

<b>Engineering controls</b>	Adequate ventilation should be provided so that exposure limits are not exceeded.
<b>Respiratory:</b>	Not normally required. If significant aerosols are likely to be generated a suitable respirator may be required. Suggested filter type AP2.
<b>Hand Protection</b>	Wear suitable chemical resistant gloves. Nitrile or neoprene gloves may be suitable, but glove manufacturers' specifications should always be checked first. Change gloves in accordance with manufacturer recommendations. If gloves are damaged during use, remove immediately and wash hands before replacing with new gloves.
<b>Skin Protection:</b>	Avoid Skin Contact; use disposable coveralls
<b>Eye Protection:</b>	Avoid Eye Contact; use safety goggles meeting the requirements of BS EN166 3, when handling this product
<b>Environmental Exposure controls</b>	Take suitable measures to prevent entry into drains, sewers and watercourses.

## SECTION 9: Physical/ Chemical Properties

### 9.1 Information on basic physical and chemical properties

<b>Appearance:</b>	Black Viscous Fluid
<b>Odor:</b>	Weak
<b>Odor threshold:</b>	No data
<b>PH:</b>	Neutral
<b>Melting Point:</b>	No data
<b>Boiling Point/ Range:</b>	338°F
<b>Flash Point;</b>	>302°F
<b>Evaporation Rate:</b>	No data
<b>Flammability:</b>	Not applicable
<b>Upper/lower flammability limits:</b>	No data
<b>Vapor Pressure:</b>	No data
<b>Vapor density:</b>	No data
<b>Relative density:</b>	1.8g/cm <sup>3</sup> at 68°F
<b>Solubility in water:</b>	Insoluble in water
<b>Solubility in other solvents:</b>	Soluble in organic solvents
<b>Partition Coefficient:</b>	Log Kow 3-5 (estimated) (Bisphenol A/F epoxy resin)
<b>Autoignition temperature:</b>	Above boiling point
<b>Decomposition temperature:</b>	No data
<b>Viscosity:</b>	Thick paste
<b>Explosive properties:</b>	Not classified as explosive
<b>Oxidizing properties:</b>	Not classified as oxidizing

### 9.2 Other information

None.

## SECTION 10: Stability And Reactivity

**10.1 Reactivity**

Not considered to be a reactive product

**10.2 Chemical stability**

Stable

**10.3 Possibility of hazardous reactions**

Hazardous Polymerization is not likely to occur.

**10.4 Conditions to avoid**

Excessive heat.

**10.5 Incompatible materials**

Acids - reaction accompanied by large heat release occurs when the product is mixed with acids

**10.6 Hazardous decomposition products**

None identified.

**SECTION 11: Toxicological Information**

**11.1 Information on toxicological effects**

This product has not been tested. Judgments on the expected toxicity of this product have been made based upon consideration of its major components.

(a) acute toxicity	Based on consideration of the components, the mixture is not expected to be harmful by inhalation, ingestion or in contact with skin. The ATE for the mixture is expected to be >2000 mg/kg
(b) skin corrosion/irritation	Based on consideration of the components, the mixture is expected to be irritating to skin.
(c) serious eye damage/irritation	Based on consideration of the components, the mixture is expected to be irritating to eyes.
(d) respiratory/skin sensitization	The product contains the following known sensitizers: Bisphenol A epoxy resin, Persons previously sensitized to amines may develop a cross sensitization reaction to certain other amines.
(e) germ cell mutagenicity	Contains no substances identified as mutagens.
(f) carcinogenicity	Contains no substances identified as carcinogens.
(g) reproductive toxicity	Resins based on Bisphenol A did not cause adverse effects in animal tests.
(h) STOT-single exposure	Target organ toxicity is not expected with this product.
(i) STOT-repeated exposure	Target organ toxicity is not expected with this product.

(j) aspiration hazard	Not applicable.
-----------------------	-----------------

**SECTION 12: Ecological Information**

This product has not been tested. Judgments on the expected toxicity of this product have been made based upon consideration of its major components.

**12.1 Toxicity**

This product contains components which are considered to be toxic to aquatic organisms and may cause long-term adverse effects in the aquatic environment. Once cured the toxicity of the product is expected to decrease.

*Data for Component: Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)*

Fish Acute & Prolonged Toxicity

LC50, Oncorhynchus mykiss (rainbow trout), semi-static test, 96 h: 2 mg/l

Aquatic Invertebrate Acute Toxicity

EC50, Daphnia magna (Water flea), static test, 48 h, immobilization: 1.8 mg/l

Aquatic Plant Toxicity

ErC50, Scenedesmus capricornutum (fresh water algae), static test, Growth rate inhibition, 72 h: 11 mg/l

Toxicity to Micro-organisms

IC50; Bacteria, 18 h: > 42.6 mg/l

Aquatic Invertebrates Chronic Toxicity Value

Daphnia magna (Water flea), semi-static test, 21 d, number of offspring, NOEC: 0.3 mg/l

**12.2 Persistence and degradability**

This product is not expected to be readily biodegradable.

*Data for Component: Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)*

Biodegradation	Exposure Time	Method	10 Day Window
12 %	28 d	OECD 302B Test	Not applicable

**12.3 Bioaccumulative potential**

This product is expected to have a low-moderate bioaccumulation potential.

**12.4 Mobility in soil**

Mobility of the uncured product is expected to be low. Cured product is expected to be immobile.

**12.5 Results of PBT and vPvB assessment**

None of the components are known to be PBT or vPvB.

**12.6 Other adverse effects**

None known.

**SECTION 13: Disposal Considerations**

**13.1 Waste treatment methods**

In uncured state, dispose as chemical waste in accordance with local regulations. Waste from this product may present long term environmental hazards. Thus landfill sites must be considered less acceptable than incineration.

In cured state when mixed correctly with the activator component, dispose as solid waste

Empty containers should be disposed of as chemical waste.

**SECTION 14: Transport Information**

**General:** Transport and labeling requirements will alter depending on the size of the packaging. Please refer to local transport regulations.

	ADR	IMDG	ICAO
14.1 UN Number	3077	3077	3077
14.2 UN Proper shipping name	Environmentally hazardous substance, solid, N.O.S. (epoxy resin)	Environmentally hazardous substance, solid, N.O.S. (epoxy resin)	Environmentally hazardous substance, solid, N.O.S. (epoxy resin)
14.3 Transport hazard class(es)	9	9	9
14.4 Packing group	III	III	III
14.5 Environmental hazards	Environmentally hazardous	Marine Pollutant	Environmentally hazardous
14.6 Special precautions for user	HIN 90	EmS F-A, S-F	None
14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable	Not applicable	Not applicable

**SECTION 15: Regulatory Information**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

All components are listed as existing substances in Europe

All components are listed, or are exempt from listing on the TCSA Inventory

**15.2 Chemical Safety Assessment**

A Chemical Safety Assessment has not been carried out for this product.

**SECTION 16: Other Information**

**Revision information:**

Reformatted in accordance with Regulation 453/2010 and Regulation 1272/2008.

**List of Abbreviations used in this SDS:**

- CAS Chemical Abstracts Service
- CLP Classification, Labeling and Packaging Regulation (EC) no 1272/2008
- DSD Dangerous Substances Directive 67/548/EEC
- DPD Dangerous Preparations Directive 1999/45/EC
- EC European Community/Commission
- PBT Persistent, Bioaccumulative and Toxic
- REACH Registration, Evaluation, Authorization and Restriction of Chemicals Regulation (EC) no 1907/2006
- vPvB very Persistent, very Bioaccumulative

**References:**

ECHA Classification and Labeling inventory



## Safety Data Sheet

ECHA database of disseminated registration dossiers  
Supplier's Safety Data Sheets

### **Method used for classification of mixtures:**

Ingredient based approaches

### **R Phrases and H Statements used in Section 3**

- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H411 Toxic to aquatic life with long lasting effects.
  
- R36/38 Irritating to eyes and skin.
- R38 May be irritating to skin
- R43 May cause sensitization by skin contact.
- R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

### **Training requirements for workers**

No special training requirements.